DC190

The Audio Video Ladibug™



The Lumens™ DC190 Ladibug™ is a high-resolution multimedia document camera that delivers crystal clear SXGA resolution with a powerful 5.5x optical zoom lens. One-touch audio/video recording and playback do not require a computer. A large image shooting area means teachers can share a view of large pages and objects instantly. The DC190 camera head and lamp are mounted on adjustable gooseneck arms to examine objects from any angle.

Key Features:

- High-Resolution XGA, SXGA, and WXGA
- One-Touch Video/Audio Recording and Playback
- Built in Microphone
- 5.5x Optical Zoom, Manual Zoom
- 8x Digital Zoom
- Annotates without a computer
- Supports Wireless mouse devices
- Internal Memory for 120 JPEG Images
- USB Drives supports up to 64 GB
- Compatible with ALL Interactive Whiteboards (IWB)
- Time-Lapse Photography
- Automatic and Manual Slide Show
- 5 Year Unlimited
 REPLACEMENT
 Warranty Lowest
 Total Cost of Ownership!
- FREE Training
- FREE Skinit Label
 Product registration required.





Specifications



DC190

IMAGING

Full screen Video/audio recording and playback

Output Resolution: XGA (1024 x 768), SXGA (1280 x 1024),

WXGA (1280 x 800)

Frame Rate: VGA - 30 fps; USB - 20 fps

Zoom Capacity: 5.5x optical zoom and 8x digital zoom

Capture Area: 18" x 12.5" (357.2 x 317.5 mm)

LIGHTING

Lamp Type: 2 lamps for completely even light coverage, (one in head)

Light Box: Optional

INPUT/OUTPUT

Power Supply: Built-in, 100-240 VAC, auto switching **VGA In:** Active pass through from the computer

VGA Out: VGA output to the projector

Audio In: Built-in microphone

Audio Out: 3.5mm phone jack for earphones or speakers Internal Memory Capacity: Up to 120 JPEG images External Memory Capacity: Support USB Drive

USB Support: USB 2.0 High Speed (up to 480 Mbps) for seamless

integration with interactive whiteboards

RS-232: Yes

C-Video: RCA Jack (PAL, NTSC)

SOFTWARE

Ladibug™ Software Included: Support PC Windows 7, XP, Vista and Mac OSX. (Free download from Lumens™ website.)

Video Recording with Audio: Record video with various compression formats. Playback with audio out- No PC needed.

Image Capture: Single or continuous capture of JPEG images.

Annotation: Add annotations directly to live image.

Controls and Operations: Same set of controls as the remote control **USB Driver**: Supports UVC, WIA and TWAIN for integration with interactive whiteboards including Promethean™, SMART™, Hitachi Starboard™, Mimio™, and others.

ACCESSORIES

Standard : Power cable, VGA cable, USB cable, Microscope adapter (x 3), Audio Cable, Remote Control

Optional: Padded carrying case, light box, USB 2.0 high speed 15

foot extension cable, 25 foot Power cable, RS232 Adapter

OPERATION FUNCTIONS

Auto Tune: Yes, single button to adjust for best possible images

Auto Exposure : Yes Auto White Balance : Yes Auto Focus : Yes

Photo/Text Mode: Choose photo/grayscale/text mode

Image Mode: Choose normal/35mm slide/microscope/negative film Image Capture: Single capturing of images to built-in memory,

or to a computer via USB, or to a USB drive

Video Recording: One-touch, Video recording and playback with audio

from built-in microphone

Picture In Picture (PIP): Yes

Freeze: Yes

Slide Show: Automatically or manually

Image Rotation: Full screen image rotation from 90,180 to 270 degrees

Annotation: Yes, Annotation with or without a computer

Spotlight : Yes Low Light Mode : Yes

Pan Across the Screen: Enlarged any part of the image and pan

it by using the arrow keys.

Mask: Yes

Projector Type: Yes, supports both LCD and DLP projectors

Volume control: Yes, via remote or OSD

SECURITY

Lock-Down Mode: Lock the unit with password entry

Auto Erase Mode: Option to automatically erase internal memory

during power down

Anti-Theft: Kensington Lock Port on document camera chassis.

Bolt Holes on Bottom for Mounting: VESA standard 2.95" x 2.95"

OTHER

Weight: 5.0 lbs (2.3kg)

Dimensions Operating : 11' x 6" x 11" (279 x 152.4x 279 mm) (L x W x H) Dimensions Folded : 7" x 6" x 11" (177.8 x 152.4x 279 mm) (L x W x H)

Warranty: 5 year unlimited REPLACEMENT warranty covers all

hardware including lamps

Express Replacement: Free advanced replacement program available

COMPLIANCE

Lumens™ comply with these important standards: FCC-EMI, cUL, CE-EMC, CE-LVD, RoHS, and WEEE.

I/O CONNECTIONS





Lumens Integration, Inc. 4116 Clipper Court Fremont, CA. 94538 Phone: (888) 542-3235

Fax: (510) 252-1389 www.MyLadibug.com Lumens Europe BVBA Assesteenweg 65. 1740 Ternat, Belgium Phone: +32 (0)2 462 61 50 Fax: +32 (0)2 462 61 53 www.Lumenseu.com

www.MyLadibug.com